# Pulmonary Function Test Filter Product Data Sheet



# **PRODUCT: Pulmonary Function Test Filter**



### **DESCRIPTION / FUNCTION**

The Flexicare Pulmonary Function Test (PFT) Filter uses electrostatic media housed within a two-piece, push fit, transparent plastic housing. Protecting both patient and pulmonary function testing equipment, the Flexicare PFT Filter reduces the risk of cross-contamination.

Use of the Flexicare PFT Filter can reduce the risk of respiratory pathogen transmission during normal breathing or forced vital capacity testing.

Minimal resistance to flow meets the American Thoracic Society (ATS) recommendations for resistance in PFT equipment, and ensures that test results are as accurate as possible.

The Flexicare PFT Filter is a single use device, designed to be fitted onto the lung function test equipment to provide a minimal resistance bacterial barrier between the patient and the machine. This reduces the risk of cross-contamination whilst also ensuring test results are as accurate as possible.

Flexicare's PFT filter is designed to be used in the hospital environment by personnel trained in the use of Pulmonary Function Test Equipment.

# **WARNINGS**

- Do not sterilise or autoclave.
- Single use device. Do not reuse.
- Do not attempt to clean this device.
- Replace this device if it becomes soiled or otherwise unfit for its application during use

### **SPECIFICATION / KEY FEATURES**

- Efficiency 99.99%
- Low Resistance 0.4cm/H20 @ 30 litres / min
- Height 250mm
- Weight 41g
- Dead Space 135ml
- 30mm ISO 5356-1 compliant connector
- Electrostatic Media
- Ergonomically incorporated mouthpiece

### **PRODUCT RANGE & PART NUMBERS**

| <b>Product Code</b>            | Description                    | Quantity |
|--------------------------------|--------------------------------|----------|
| Pulmonary Function Test Filter |                                |          |
| 038-41-395                     | Pulmonary Function Test Filter | 50       |
| Optional accessory             |                                |          |
| 038-41-394                     | Nose Clip                      | 50       |

### **MATERIALS**

| Component                  | Material                                  |
|----------------------------|---|
| Filter Housing             | Polypropylene (PP)                        |
| Electrostatic Filter Media | Polypropylene (PP)/ synthetic fibre blend |
| Nose Clip                  | Polypropylene (PP), Silicone              |

# **LATEX CONTENT**

Flexicare's Pulmonary Function Test (PFT) Filter does not contain natural rubber latex.

### **DEHP CONTENT**

Flexicare's Pulmonary Function Test (PFT) Filter does not contain phthalate DEHP.

### **SINGLE USE**

Flexicare's Pulmonary Function Test (PFT) Filter is a Single Use device and should be disposed of after use. Do not sterilise or autoclave.

### **STERILITY**

Flexicare's Pulmonary Function Test (PFT) Filter is supplied non-sterile.

### **STORAGE**

Store in a cool, dry place out of direct sunlight.

### **SHELF LIFE**

Flexicare declares a shelf life of five years from the date of manufacture. This is based on the stability of the devices' components and raw materials sourced. Expiry date is clearly marked on individual product packaging.

# **DISPOSAL CONSIDERATIONS**

Dispose as clinical waste, in accordance with hospital policy, local guidelines and regulations.

# **PACKAGING MATERIALS**

Primary – Polybag – Low Density Polyethylene (LDPE)

Secondary – Carton / Box - Cardboard